

0.1 - 8mm Expanded Metal Grating With Precise Specifications 50m/roll

Basic Information

. Place of Origin: **CHINA** . Brand Name: YUDA

Model Number: Expanded metal mesh

 Minimum Order Quantity: 50 Meters

• Price: US \$2.50 - 5.60/ Square Meter Packaging Details: Customized according to buyer's

requirements

. Delivery Time: 3-10 day

• Payment Terms: T/T, L/C, D/A, D/P, Western Union,

MoneyGram

200000 Meters/ day • Supply Ability:



Product Specification

• Product Name: Expanded Metal Mesh • Key Words: With Precise Specifications

Material: Low Carbon Steel /stainless Steel /

Aluminum/copper Etc.

. Hole Shape: Diamond Hole, Hexagonal, Etc,

• Thickness: 0.1 - 8mm Or Custom

Length: 1-50m/roll, Customers' Requirement Width: 0.5-2m, Customers' Requirement


• Wire Diameter: Requirement

• Highlight: 8mm expanded metal grating,

50m/roll expanded metal grating



More Images



Product Description

Expanded Metal Grating With Precise Specifications

Materials: Common expanded metal mesh materials include steel, aluminium, stainless steel and so on. The specific choice of material should take into account the application environment and requirements.

Aperture size: refers to the size of the mesh holes, usually in millimetres (mm). The size of the mesh can be determined by the required filtration, ventilation or protection requirements.

Plate Thickness: refers to the thickness of the metal mesh, usually in millimetres (mm).

Mesh Size: refers to the overall size of the expanded metal mesh and can be determined based on the space requirements of the specific application.

Plate Width and Length: Expanded metal mesh is usually made in the form of a full sheet of metal, so plate width and length are also important specification parameters.

Hole Shape: Expanded metal mesh can be drilled, diamond holes, square holes, etc. The specific shape can be selected according to the application requirements.

Surface treatment: Expanded metal mesh can be surface treated, such as hot-dip galvanised, sprayed, etc., to provide additional corrosion resistance and aesthetics.

Common specification of Expanded Metal Walkway Grating					
Thickness	Strand width	SW	LWD		
		D		SW(m	LW(m
(mm)	(mm)	(m	(mm)	m)	m)
		m)			
5	6.5	30	75	2000	600
5	6.5	30	80	2300	750
5	7.5	36	100	1800	900
5	7.5	36	136	3000	1200
5	8	40	100		
5	8	40	120		
5	11	55	100		
5	11	55	135		









