




## New High Tensile Self Adhesive Mosaic Tile Wall Meshes Roll Customizable E-Glass

### Our Product Introduction

for more products please visit us on [wire-metalmesh.com](http://wire-metalmesh.com)


#### Basic Information

- Place of Origin: CHINA
- Brand Name: YUDA
- Certification: IOS
- Model Number: Glass fibre mesh
- Minimum Order Quantity: 100 Square Meter
- Price: US \$0.15 - 0.35/ Square Meter
- Packaging Details: Customized according to buyer's requirements
- Delivery Time: 3-10 day
- Payment Terms: L/C, D/A, D/P, T/T, Western Union, MoneyGram
- Supply Ability: 5000 rolls/ day




#### Product Specification

- Product Name: Fiberglass Mesh
- Key Words: New High Tensile Self Adhesive Mosaic Tile Wall Meshes Roll Customizable E-Glass
- Size: Can Be Custom Made
- Fiberglass Yarn: E-Glass
- Coating: Acrylic Glue / SBR Glue
- Roll Width: 1.2m/1.8m.
- Sample: Free
- Label: Can Be Customized
- Highlight: **High Tensile Self Adhesive Mosaic Tile, Customizable Self Adhesive Mosaic Tile, E-Glass Self Adhesive Mosaic Tile**



#### More Images




## Product Description

### New High Tensile Self Adhesive Mosaic Tile Wall Meshes Roll Customizable E-Glass

#### Introduction of alkali-resistant grid cloth:

1. Good chemical stability. Alkali resistance, acid resistance, water resistance, cement erosion resistance, and other chemical corrosion resistance; strong adhesion to resin, soluble in styrene, etc. 2. High strength, high modulus and light weight. 3. Good dimensional stability, stiff, smooth, not easy to shrink and deform, and good positioning. 4. Good impact resistance. (Because the mesh cloth has high strength and good toughness) 5. Anti-mildew and insect-proof.

## Product testing



45g/m<sup>2</sup> 3mm\*3mm



80g/m<sup>2</sup> 5mm\*5mm



135g/m<sup>2</sup> 5mm\*5mm



160g/m<sup>2</sup> 4mm\*4mm

Reinforced Fiberglass Wall Mesh Specification:

Item Number	Yarn(Tex )		Mesh(m m)		Density Count/25mm		Tensile Strength × 20cm		Woven Structure	Content of resin%
	Warp	Weft	Warp	Weft	Warp	Weft	Warp	Weft		
45g2.5x2.5	33x2	33	2.5	2.5	10	10	550	300	Leno	18
60g2.5x2.5	40x2	40	2.5	2.5	10	10	550	650	Leno	18
70g 5x5	45x2	200	5	5	5	5	550	850	Leno	18
80g 5x5	67x2	200	5	5	5	5	700	850	Leno	18
90g 5x5	67x2	250	5	5	5	5	700	1050	Leno	18
110g 5x5	100x2	250	5	5	5	5	800	1050	Leno	18
125g 5x5	134x2	250	5	5	5	5	1200	1300	Leno	18
135g 5x5	134x2	300	5	5	5	5	1300	1400	Leno	18
145g 5x5	134x2	360	5	5	5	5	1200	1300	Leno	18
150g 4x5	134x2	300	4	5	6	5	1300	1300	Leno	18
160g 5x5	134x2	400	5	5	5	5	1450	1600	Leno	18
160g 4x4	134x2	300	4	4	6	6	1550	1650	Leno	18
165g 4x5	134x2	350	4	5	6	5	1300	1300	Leno	18

### Main characteristics

1. Good chemical stability: Alkali-resistant, acid-resistant, waterproof,, cement erosion-resistant, and other chemicals' corrosion resistant; and strong resin bonding, soluble in styrene.
2. Good dimensional stability, stiffness, smoothness an difficult to shrink and deformation, good positioning property..
3. Good impact resistance and not easy to be teared.
4. Fire resistant, thermal insulation, sound insulation, insulations etc.



Fiberglass Mesh



Drywall Self-Adhesive Tape



Fiberglass Yarn

1. 75g / m2 mesh fabric used in the reinforcement of thin slurry, to eliminate small cracks and scattered throughout the surface pressure.
2. 110g / m2 mesh cloth is widely used in indoor and outdoor walls, prevent the various materials (such as brick, light wood, prefabricated structure) of treatment or caused by a variety of expansion coefficient of wall crack and break .
3. 145g/m2 mesh fabric used in the wall and be mixed in various materials (such as brick, light wood, prefabricated structures), to prevent cracking and scatter the whole surface pressure, especially in the external wall insulation system (EIFS ).
4. 160g / m2 mesh fabric used in insulator layer of reinforcement in the mortar, through shrinkage and temperature changes by providing a space to maintain movement between the layers, prevent crack and rupture due to shrinkage or temperature change.





**Anping Yuda Wire Mesh Co., Ltd.**



13785885555



[sales@china-mesh-wire.com](mailto:sales@china-mesh-wire.com)



[wire-metalmesh.com](http://wire-metalmesh.com)

Xiwangzhuang Developing Zone, Anping, Hebei, China